



SM07J Rear Vision System

Our OEM and Fleet proven 7-inch Digital Screen with ultra-clear image in our custom housing. Verity systems are constantly upgraded with the latest in Accident Avoidance technology remain the same in size and compatible with our previous components. 20 years of installs, factory line audits, tech support, warranty, and a lifetime of "it would work better and longer if we could..." went into the development of this system. 99.7 % of our systems are working flawlessly...we want 100%!

MONITOR SPECIFICATIONS MK07J

Screen size: 7-inch digital screen (16:9)

Long Life High Resolution: 800 x 480 Pixel (RGB)

System: PAL/NTSC auto select

Contrast: 500:1

Brightness: 450 cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperature: -30°~70°C

Storage temperature: -40°~80°C

61" monitor harness with 2 AV color-coded aviation/waterproof connections, waterproof fuse and color-coded trigger wires.

Auto blue screen if no signal on activated channel.

Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: image delay on time 0~10s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel, multi-language, featuring adjustable guidelines.



CAMERA SPECIFICATIONS C001J

Horizontal Resolution: 700 TV Lines

TV System: NTSC

Image Type: 1/3 Inch Color CCD Sharp® or equivalent -
(no cheap off brands used)

Effective pixel: NTSC:510(H) x 492(V)

Illumination: 0 Lux (built-in 20 high output IR LEDs for night vision)

Aluminum housing. Waterproof: IP69K

Power supply: 12V DC (from monitor)

Shockproof: 10G

Operating temperature: -40~70°C

Audio and IR night vision, Viewing angle: 120°

Optional ADD100ZV

Aluminum Camera Cover

Available for J-series Camera



574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Rev. 4 19

Subject to change without notice