

SM05J **Rear Vision System**

Our OEM and Fleet proven 5-inch Digital Screen with ultra-clear image in our custom housing. Verity systems are constantly upgraded with the latest in Accident Avoidance technology remain the same in size and compatible with our previous components. 20 years of installs, factory line audits, tech support, warranty, and a lifetime of "it would work better and longer if we could..." went into the development of this system. 99.7 % of our systems are working flawlessly...we want 100%!

MONITOR SPECIFICATIONS MK05J

Screen size: 5-inch digital screen (16:9)

Long Life High Resolution: 640 x 480 Pixel (RGB)


System: PAL/NTSC auto select

Contrast: 400:1

Brightness: 450 cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperature: -30°~70°C Storage temperature: -40°~80°C



Auto blue screen if no signal on activated channel. Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: image delay on time 0~10s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel, multi-language, featuring adjustable guidelines.

CAMERA SPECIFICATIONS C001J

- COLOR CCD CAMERA -
- Highest quality available
- Shockproof: 10G
- Built-in waterproof microphone
- Waterproof: IP69K for extreme environment Viewing angle: 130° (To meet FMVS111 requirements, request our C300P camera)
- Format is NTSC to ensure proper images with USA formatted DVRs
- Resolution: 700TV Lines / Effective pixel: 510 x 492
- Illumination: 0 Lux (20 high flood output IR LEDs for broad view night vision)
- Power supply: DC 12V (powered by monitor)

Optional ADD100Z

Aluminum Camera Cover Available for J-series Camera







Serving OEMs & Fleets

574-807-6002

www.verityrvs.com

Est. 2002

Women-Owned

A division of Component Solution Services, LLC.

Subject to change without notice

56600 Twin Branch Dr., Mishawaka, IN 46545

Rev. 4 19